# ISX™ 2200

## Ferris ISX™ 2200

The Oil Guard system extends the interval required between oil changes from 100 hours to 500 hours, saving you time and money when it comes to oil maintenance. Oil Guard is the only turf engine system that continuously exchanges oil between the engine and a large external reservoir, to shield engine oil from thermal breakdown, resulting in a cooler-running engine, ensures proper lubrication during off-angle operation, mess-free oil change and extends oil service intervals, which translates to increased productivity!

- Vanguard® EFI engine
- Foot-operated and spring-assisted deck lift system
- iCD™ deck technology
- Coil-Over-Shocks
- Forefront™ Independent front wheel suspension
- TRIPLE mower deck
- **Comes with 3-Year warranty***



**£17,100**
PLUS VAT
FM-IS-5902030

SCAN ME FOR MORE

| **ACCESSORIES** DESCRIPTION | PRODUCT CODE | PRICE |
|---|---|---|
| Lighting kit | F-LIGHTING KIT 2021 | **POA** |
| Agricultural tyres EACH | F-24X12-12 AG | **£193.00** |
| Rotating beacon and pole | F-BEACON/POLE | **£212.00** |
| Micro beacon | Z-MICRO BEACON KIT | **£284.00** |
| Solid front castor tyres EACH | 5109903 | **£235.00** |
| Service stand kit | 5601077/80 | **£265.00** |
| Trailer hitch kit | 5600031 | **£72.00** |

# ISX™ 2200

| SPECIFICATION | |
|---|---|
| **Engine** | |
| Make | Vanguard™ – Petrol |
| Model | MOD49, 810 Series |
| Horsepower | 28.0 gross HP2) / 20.9 gross kW @3600rpm |
| Cylinders / Displacement | 2 Cylinders V-Twin / 810 cc |
| Cooling | Air cooled |
| PTO | Warner CMS Clutch-Brake (271 Nm) |
| Starting | Electric |
| Fuel Capacity | 42 Litres |
| **Mower** | |
| Cutting width (cm/inch) | [1]55 cm / 61" Triple iCD™ |
| Deck Configuration | Configurable deck including: rear discharge, side discharge, mulching and mulching blades |
| Cutting Height (cm) | 38 – 127 mm |
| Deck Construction | 3,4 mm fabricated construction, full width double top deck, metal scuff guards, reinforced leading edge, overlap welded corners |
| Mower Spindles | Cast-iron Ø201 mm; Ø25,4 mm shaft |
| Deck lift system | Foot pedal, spring assisted |
| **Suspension & Drive Train** | |
| Suspension | Rear and front wheel suspension system with adjustable coil-over-shocks |
| Transmission | Independent Hydro-Gear® ZT-4400™ transaxles |
| Drive Axles | 34,93 mm drive shaft with 5 bolt wheel hub |
| Drive Tyres (inch) | 23 x 10.50 – 12 drive tyres (4 ply) Pneumatic tyre w. turf tread |
| Caster Tyres (inch) | 13 x 6.5 – 6 caster tyres (4 ply) Pneumatic tyre w. smooth tread |
| **Noise and Vibration** | |
| HAV | < 2.5 |
| WBV | < 0.5 |
| Sound dB(A) | 105 |
| **Ground Speed** | |
| Speed-fwd. (km/h) | 0 – 18,0 km/h |
| Speed-rev. (km/h) | 0 – 8 km/h |
| **Dimensions** | |
| Overall length (cm) | 213.5 |
| Overall width (cm) | RD: 161,5 – SD: 167,5 / 201,5 (Deflector up / Deflector down) |
| Dry weight (Kgs) | 639kg |
| **Operator Control & Comfort Systems** | |
| Roll-Over Protection Structure | Standard, foldable with retractable seat belt |
| Instrumentation | Fuel level gauge in each tank, hour meter, engine malfunction indicator |
| Controls | Seat activated engine kill, PTO clutch safety switch, neutral and parking brake safety circuit |
| Parking Brake / Safety Circuit | Internal wet disc brake in transaxle |
| **Warranty*** | |
| Mower | 3-Year Manufacturer's Limited Warranty/300 hours, whichever comes first. Parts and labour in year one, parts only in years 2 and 3. |
| Coil-over-shocks | 4-Year (48 months) unlimited hours (including all suspension related components) |
| Engine | 3-Year manufacturer's limited warranty |
| Transmission | 2-Year manufacturer's limited warranty |

YOUR NEAREST AUTHORISED FERRIS DEALER IS:

**ferrismowers.co.uk**

Specifications and prices are subject to change without notice | © T H WHITE 2024 | IMP-FPS-0724