



FW25

FW25: the compact and manoeuvrable walk-behind

The Ferris FW25 dual hydrostatic walk behind mower was built from the ground up offering high performance and strong build quality. It meets the demands of professional mowing crews by providing a smooth and user friendly operation. The FW25 also boasts an impressive 18.5 Kawasaki engine adding improved reliability and performance. The 36" rear discharge deck is small enough to work nimbly in confined spaces and compact enough to transport easily.

This model is a revamp of the already popular FW35, featuring an upgraded cruise control and independent steering system. This walk-behind mower provides easier deck levelling to allow easy access to grease points and more durable water points for reduced maintenance.

- Cruise control bar
- Park brake handle
- Robust engine deck
- Deck drive belt system
- Heavy-duty transmission guards
- Deck mounting system
- **Comes with 2-Year warranty***



£9,670
PLUS VAT
5901869



SCAN ME FOR MORE ▶

ACCESSORIES DESCRIPTION	PRODUCT CODE	PRICE
Agricultural tyres EACH	F-K378	£145.00
Wide fast trax wheels EACH	18 x 11 - 10 CFT	£325.00
Twin wheel kit	DUAL WHEEL KIT 1	£870.00
Front weight kit	F-5600971	£262.00
Service stand mounting	5601286	£118.00
Service stand	5601080	£178.00
Solid front castor wheels EACH	5100790	£110.00



FW25

SPECIFICATION	
Engine	
Make	Kawasaki – Petrol
Model	FS600V
Horsepower	18.5 HP
Cylinders / Displacement	2 Cylinders V-Twin / 603 cc
Cooling	Air cooled
PTO	Electric PTO clutch
Starting	Electric
Fuel Capacity	19 Litres
Mower	
Cutting width (cm/inch)	91 cm / 36" Rear Discharge
Deck Configuration	Rear discharge/mulching insert and mulching blades
Cutting Height (cm)	3,8 – 11,4 cm
Deck Construction	3.4 mm fabricated construction, full width double top deck, 4,8 mm scuff guards, 9.5mm leading edge, overlap welded corners
Mower Spindles	Cast aluminium 133 mm; 25,4 mm shaft
Deck lift system	Central height adjustment with double hand wheels
Suspension & Drive Train	
Suspension	N/A
Transmission	Independent Hydro-Gear® ZT-3100™ transaxles
Drive Axles	25,4 mm Tapered with 4-bolt flange
Drive Tyres (inch)	20 x 7.00 – 10 (4 ply)
Caster Tyres (inch)	11 x 4.00 – 5 (4 ply)
Noise and Vibration	
HAV	< 2.5
WBV	N/A
Sound dB(A)	100
Ground Speed	
Speed-fwd. (km/h)	0 – 9,6 km/h
Speed-rev. (km/h)	0 – 9,6 km/h
Dimensions	
Overall length (cm)	198
Overall width (cm)	94
Dry weight (Kgs)	288
Operator Control & Comfort Systems	
Roll-Over Protection Structure	N/A
Instrumentation	Speed indicator, hour meter
Controls	Operator presence, cruise control bar, independent forward and reverse levers, foot activated neutral
Parking Brake / Safety Circuit	Integrated transaxle brake
Warranty*	
Engine	2-Year limited warranty commercial use. Unlimited Hours
Transmission	2-Year manufacturer's limited warranty
Balance of machine	2-Year Limited Warranty commercial use. Unlimited hours, front to rear, parts and labour. Belts, Tyres, Brake Pads, Battery, Blades: 90 days

YOUR NEAREST AUTHORISED FERRIS DEALER IS:

ferrismowers.co.uk