



ISX™ 2200

Ferris ISX™ 2200

Featuring the next generation of Ferris suspension technology – ForeFront™ Suspension, a 2-belt iCD™ cutting system, heavy-duty Hydro-Gear® ZT-4400™ Transaxle drive system and travel speeds up to 10 mph, the ISX™ 2200 is engineered to increase efficiency and operator comfort. Spend one day on the ISX™ 2200 zero-turn mower and you will discover how our patented suspension technology turns slow and bumpy mowing into riding comfort and enhanced productivity. With TRIPLE mowing technology under the mower deck, you'll enjoy unique versatility that's all available in one package!

- Vanguard® EFI engine
- Foot-operated and spring-assisted deck lift system
- iCD™ deck technology
- Coil-Over-Shocks
- Forefront™ Independent front wheel suspension
- TRIPLE mower deck
- **Comes with 3-Year warranty***



£17,780
PLUS VAT

FM-IS-5902030



SCAN ME FOR MORE ▶

ACCESSORIES	DESCRIPTION	PRODUCT CODE	PRICE
	Lighting kit	F-LIGHTING KIT 2021	£1300.00
	Agricultural tyres EACH 52" deck	F-24X12-12 AG	£195.00
	Rotating beacon and pole	F-BEACON/POLE	£225.00
	Micro beacon	Z-MICRO BEACON KIT	£305.00
	Solid front castor tyres EACH	5109903	£260.00
	Service stand kit	5601077/80	£280.00
	Agricultural tyres EACH 61" deck	24x12-12AG	£204.00



ISX™ 2200

SPECIFICATION	
Engine	
Make	Vanguard™ – Petrol
Model	MOD49, 810 Series
Horsepower	28.0 gross HP2) / 20.9 gross kW @3600rpm
Cylinders / Displacement	2 Cylinders V-Twin / 810 cc
Cooling	Air cooled
PTO	Warner CMS Clutch-Brake (271 Nm)
Starting	Electric
Fuel Capacity	42 Litres
Mower	
Cutting width (cm/inch)	155 cm / 61" Triple iCD™
Deck Configuration	Configurable deck including: rear discharge, side discharge, mulching and mulching blades
Cutting Height (cm)	38 – 127 mm
Deck Construction	3,4 mm fabricated construction, full width double top deck, metal scuff guards, reinforced leading edge, overlap welded corners
Mower Spindles	Cast-iron Ø201 mm; Ø25,4 mm shaft
Deck lift system	Foot pedal, spring assisted
Suspension & Drive Train	
Suspension	Rear and front wheel suspension system with adjustable coil-over-shocks
Transmission	Independent Hydro-Gear® ZT-4400™ transaxles
Drive Axles	34,93 mm drive shaft with 5 bolt wheel hub
Drive Tyres (inch)	23 x 10.50 – 12 drive tyres (4 ply) Pneumatic tyre w. turf tread
Caster Tyres (inch)	13 x 6.5 – 6 caster tyres (4 ply) Pneumatic tyre w. smooth tread
Noise and Vibration	
HAV	< 2.5
WBV	< 0.5
Sound dB(A)	105
Ground Speed	
Speed-fwd. (km/h)	0 – 18,0 km/h
Speed-rev. (km/h)	0 – 8 km/h
Dimensions	
Overall length (cm)	213.5
Overall width (cm)	RD: 161,5 – SD: 167,5 / 201,5 (Deflector up / Deflector down)
Dry weight (Kgs)	639kg
Operator Control & Comfort Systems	
Roll-Over Protection Structure	Standard, foldable with retractable seat belt
Instrumentation	Fuel level gauge in each tank, hour meter, engine malfunction indicator
Controls	Seat activated engine kill, PTO clutch safety switch, neutral and parking brake safety circuit
Parking Brake / Safety Circuit	Internal wet disc brake in transaxle
Warranty*	
Mower	3-Year Manufacturer's Limited Warranty/300 hours, whichever comes first. Parts and labour in year one, parts only in years 2 and 3.
Coil-over-shocks	4-Year (48 months) unlimited hours (including all suspension related components)
Engine	3-Year manufacturer's limited warranty
Transmission	2-Year manufacturer's limited warranty

YOUR NEAREST AUTHORISED FERRIS DEALER IS: