



ISX™ 3300

Ferris ISX™ 3300 Zero Turn Mowers

THE LEADER IN SUSPENSION TECHNOLOGY FOR TURF. Featuring next-generation suspension technology – ForeFront™ Suspension, a redesigned 2-belt iCD™+ cutting system, heavy-duty dual commercial Hydro-Gear® ZT-5400 drive system, and travel speeds up to 12 mph. Plus, select models feature EFI-ETC technology for fuel savings, easy starting, and smooth, consistent productivity.

The ISX™ 3300 also benefits from the Vanguard Oil Guard™ System, a first of its kind solution in the industry and exclusive to Ferris Vanguard EFI engine mowers. The Oil Guard system extends the interval required between oil changes from 100 hours to 500 hours, saving you time and money when it comes to oil maintenance. Oil Guard is the only turf engine system that continuously exchanges oil between the engine and a large external reservoir, to shield engine oil from thermal breakdown, resulting in a cooler-running engine, ensures proper lubrication during off-angle operation, mess-free oil change and extends oil service intervals, which translates to increased productivity!



- NEW! iCD+™ Cutting System
- NEW! USB Port
- ForeFront™ Suspension System
- Vanguard BIG BLOCK™ Engine
- Vanguard Electronic Throttle Control
- **Comes with 4-Year warranty***

£20,750
PLUS VAT
FM-IS-5902036-5901917(61*)



SCAN ME FOR MORE ▶

ACCESSORIES	DESCRIPTION	PRODUCT CODE	PRICE
	Lighting kit (inc, day running lights, headlight, main beam, indicators, horn, number plate lights, flashing beacon)	F-LIGHTING KIT 2021	£1300.00
	Agricultural tyres EACH	F-23X10.50-12AG	£245.00
	Rotating beacon and pole	F-BEACON/POLE	£230.00
	Micro beacon	Z-MICRO BEACON KIT	£305.00
	Solid front castor tyres EACH	5109903	£260.00
	Service stand kit	5601235/79/80	£365.00
	Trailer hitch kit	5600860	£70.00



ISX™ 3300

SPECIFICATION	
Engine	
Make	Vanguard™ – Petrol
Model	BIG BLOCK™ EFI
Horsepower	37 HP
Cylinders / Displacement	2 Cylinders V-Twin / 993 cc
Cooling	Air cooled
PTO	Electric PTO clutch
Starting	Electric
Fuel Capacity	42 Litres
Mower	
Cutting width (cm/inch)	155 cm / 61" Rear Discharge iCD™
Deck Configuration	Rear discharge/mulching insert and mulching blades
Cutting Height (cm)	3,8 – 12,7 cm
Deck Construction	3,4 mm fabricated construction, full width double top deck, 12,7 mm scuff guards, 12,7 mm leading edge, overlap welded corners
Mower Spindles	Hercules II Cast-iron 257 mm; 30,16 mm shaft
Deck lift system	Hydraulic
Suspension & Drive Train	
Suspension	4-Wheel independent suspension
Transmission	Independent Hydro-Gear® ZT-5400™ transaxles
Drive Axles	34,93 mm drive axles with 5 bolt wheel hubs
Drive Tyres (inch)	26 x 12.00 – 12 (4 ply)
Caster Tyres (inch)	13 x 6.50 – 6 (4 ply)
Noise and Vibration	
HAV	< 2.5
WBV	< 0.5
Sound dB(A)	105
Ground Speed	
Speed-fwd. (km/h)	0 – 12 km/h
Speed-rev. (km/h)	0 – 5 km/h
Dimensions	
Overall length (cm)	215
Overall width (cm)	169
Dry weight (Kgs)	752
Operator Control & Comfort Systems	
Roll-Over Protection Structure	Standard, 165-degrees foldable with seat belt
Instrumentation	Fuel level gauge in each tank, hour meter, engine malfunction indicator
Controls	Seat activated engine kill, clutch safety switch, neutral and parking brake safety circuit, adjustable twin steering controls
Parking Brake / Safety Circuit	Superior quality seat with adjustable arm-rests and multi-position headrest
Warranty*	
Mower	4-Year limited warranty (48 months or 500 hours) whichever occurs first. Unlimited hours during the first 2 years (24 months)
Coil-over-shocks	5-Year (60 months) unlimited hours (including all suspension related components)
Engine	3-Year manufacturer's limited warranty
Transmission	2-Year manufacturer's limited warranty
Consumables	90 days (including drive belts, tyres, brakes, deck rollers, battery, blades)

YOUR NEAREST AUTHORISED FERRIS DEALER IS:

ferrismowers.co.uk