



# ISX™800

## Ferris ISX™800

The ISX™800 is powered by a Briggs & Stratton Commercial Turf™ 27-gross HP, 810cc V-Twin petrol engine, featuring a commercial warranty of 3 years. If you are looking for the best value in a compact zero-turn mower, look no further than the Ferris ISX™800. Featuring our patented suspension now with innovative double wishbone system, iCD™ cutting deck technology, heavy-duty Hydro-Gear® drive system, an engine purpose built for a zero-turn application and mowing speeds up to 16 km/h.

- Commercial Turf Series™
- Double Wishbone Suspension
- Hydro-Gear® ZT-3400 transaxles
- Double Belt Drive System
- Large Drive Tyres
- 180 degree folding ROPS
- **Comes with 3-Year warranty\***



**£12,350**  
PLUS VAT

FM-IS-5902021



SCAN ME FOR MORE ▶

| ACCESSORIES | DESCRIPTION                   | PRODUCT CODE        | PRICE           |
|-------------|-------------------------------|---------------------|-----------------|
|             | Lighting kit                  | F-LIGHTING KIT 2021 | <b>£1300.00</b> |
|             | Agricultural tyres EACH       | F-23X10.50-12AG     | <b>£150.00</b>  |
|             | Micro beacon                  | Z-MICRO BEACON KIT  | <b>£305.00</b>  |
|             | Solid front castor tyres EACH | 5109903             | <b>£250.00</b>  |
|             | Service stand kit             | 5601235/80          | <b>£280.00</b>  |
|             | Trailer hitch kit             | 5600031             | <b>£78.00</b>   |



# ISX™800

| SPECIFICATION                                 |   |
|---|---|
| <b>Engine</b>                                 |   |
| Make  | Briggs & Stratton – Petrol  |
| Model   | Commercial Series   |
| Horsepower                                    | 27 HP   |
| Cylinders / Displacement                      | 2 Cylinders V-Twin / 810 cc   |
| Cooling                                       | Air cooled  |
| PTO   | Electric PTO clutch   |
| Starting                                      | Electric  |
| Fuel Capacity                                 | 21 Litres   |
| <b>Mower</b>                                  |   |
| Cutting width (cm/inch)                       | 132 cm / 52"  |
| Deck Configuration                            | Rear Discharge with mulching insert and mulching blades   |
| Cutting Height (cm)                           | 38 – 127 mm   |
| Deck Construction                             | 3,4 mm fabricated construction, full width double top deck, 9,5mm scuff guards, overlap welded corner                               |
| Mower Spindles                                | Cast iron 201mm, 25,4mm shaft   |
| Deck lift system                              | Foot pedal, spring assisted   |
| <b>Suspension &amp; Drive Train</b>           |   |
| Suspension                                    | Rear and front wheel suspension system with adjustable coil-over-shocks   |
| Transmission                                  | Independent Hydro-Gear® ZT-3400™ transaxles   |
| Drive Axles                                   | 28,6 mm Tapered with 4-bolt flange  |
| Drive Tyres (inch)                            | 23 x 10.50 – 12 drive tyres (4 ply)   |
| Caster Tyres (inch)                           | 13 x 6.5 – 6 caster tyres (4 ply)   |
| <b>Noise and Vibration</b>                    |   |
| HAV   | < 2.5   |
| WBV   | < 0.5   |
| Sound dB(A)                                   | 105   |
| <b>Ground Speed</b>                           |   |
| Speed-fwd. (km/h)                             | 0 – 16 km/h   |
| Speed-rev. (km/h)                             | 0 – 8 km/h  |
| <b>Dimensions</b>                             |   |
| Overall length (cm)                           | 211   |
| Overall width (cm)                            | 135   |
| Dry weight (Kgs)                              | 487kg   |
| <b>Operator Control &amp; Comfort Systems</b> |   |
| Roll-Over Protection Structure                | Standard, foldable with retractable seat belt   |
| Instrumentation                               | Fuel level gauge, hour meter  |
| Controls                                      | Seat activated engine kill, PTO clutch safety switch, neutral and parking brake safety circuit                                      |
| Parking Brake / Safety Circuit                | Integrated transaxle brake  |
| <b>Warranty*</b>                              |   |
| Mower   | 3-Year Manufacturer's Limited warranty/300 hours, whichever comes first. Parts and labour in year one, parts only in years 2 and 3. |
| Coil-over-shocks                              | 4-Years (48 months) unlimited hours (including all suspension related components)   |
| Engine  | 3-Year manufacturer's limited warranty  |
| Transmission                                  | 2-Year manufacturer's limited warranty  |
| Consumables                                   | 90 days (including drive belts, tyres, brakes, deck rollers, battery, blades)   |

YOUR NEAREST AUTHORISED FERRIS DEALER IS:

[ferrismowers.co.uk](http://ferrismowers.co.uk)