



IS[®]2600Z

Ferris IS[®]2600Z 61" TRIPLE ICD[™]

The IS[®]2600Z zero turn mower series continues to expand the Ferris zero turn lineup offering diesel power with features and benefits that no other commercial mower can. When our engineers set out to refresh the successful previous model, the IS[®]2500Z, taking into consideration the requirements of end users, the resulting lawn machine is rugged yet refined. There is not another product in its class that can match the value this zero turn mower offers, especially when paired with the benefits of Ferris' patented mower suspension system. The entire system responds to the most unforgiving terrain with refined control and incomparable steering accuracy, softening the jolts and lessening the stress on both man and machine.

The IS[®]2600Z's efficient Yanmar[™] 3 cylinder diesel engine complies with the Stage 5 EU Emission Legislation.



- Dual coil-over-shock rear suspension
- Foot-operated hydraulic deck lift system
- Yanmar[™] 3 cylinder diesel engine
- Quick removeable floor plate
- NEW! iCD+[™] Cutting System
- Cast-iron mower spindles
- **Comes with 4-Year warranty***

£23,860
PLUS VAT
5901931



SCAN ME FOR MORE ▶

ACCESSORIES	DESCRIPTION	PRODUCT CODE	PRICE
	Lighting kit (inc. side lights & indicators)	F-LIGHTING KIT 2021	£13000.00
	Agricultural tyres EACH 61" deck	24X12-12AG	£204.00
	Rotating beacon and pole	5F-BEACON/POLE	£225.00
	Micro beacon	Z-MICRO BEACON KIT	£305.00
	Solid front castor wheels EACH	5109903	£260.00
	Service stand kit	5601077/80	£280.00



IS[®] 2600Z

SPECIFICATION	
Engine	
Make	Yanmar – Diesel, EPA FINAL TIER 4
Model	3TNM74F-SAFS
Horsepower	24 HP
Cylinders / Displacement	3 Cylinders in line /993 cc
Cooling	Liquid Cooled
PTO	Electric PTO clutch
Starting	Electric
Fuel Capacity	42 Litres
Mower	
Cutting width (cm/inch)	155 cm / 61" Rear Discharge iCD™
Deck Configuration	Rear discharge/mulching insert and mulching blades
Cutting Height (cm)	3,8 – 12,7 cm
Deck Construction	3,4 mm fabricated construction, full width double top deck, 12,7 mm scuff guards, 9,5 mm leading edge, overlap welded corners
Mower Spindles	Cast-iron 201 mm; 25,4 mm shaft
Deck lift system	Foot pedal, spring assisted
Suspension & Drive Train	
Suspension	4-Wheel independent suspension
Transmission	Independent Hydro-Gear® ZT-4400™ transaxles
Drive Axles	34,93 mm drive axles with 5 bolt wheel hubs
Drive Tyres (inch)	24 x 12.00 – 12 (4 ply)
Caster Tyres (inch)	13 x 6.50 – 6 (4 ply)
Noise and Vibration	
HAV	< 2.5
WBV	< 0.5
Sound dB(A)	105
Ground Speed	
Speed-fwd. (km/h)	0 – 18.0 km/h
Speed-rev. (km/h)	0 – 8.0 km/h
Dimensions	
Overall length (cm)	224
Overall width (cm)	159
Dry weight (Kgs)	743kg
Operator Control & Comfort Systems	
Roll-Over Protection Structure	Standard, foldable with seat belt
Instrumentation	Fuel level gauge in each tank, visual water temperature gauge, oil pressure gauge, hour meter
Controls	Seat activated engine kill, PTO clutch safety switch, neutral and parking brake safety circuit, deck shutdown engine protection system
Parking Brake / Safety Circuit	Internal wet disc brake in transaxle
Warranty*	
Engine	2-Year Manufacturer's Limited Warranty)
Transmission	2-Year Manufacturer's Limited Warranty
Balance of machine	4-Year Limited Warranty (48 months) or 500 hours, whichever occurs first. Unlimited hours during the first 2 years (24 months). Coil-over-shocks and all suspension related components are covered for 4 years (48 months) unlimited hours. Belts, Tires, Brake Pads, Battery, Blades: 90 days

YOUR NEAREST AUTHORISED FERRIS DEALER IS:

ferrismowers.co.uk