



# IS<sup>®</sup> 600Z

## Ferris IS<sup>®</sup> 600Z

The Ferris IS<sup>®</sup> 600Z features our patented suspension technology, heavy-duty Hydro-Gear<sup>®</sup> drive system, an engine purpose built for a zero-turn application and mowing speeds up to 14,5 km/h. This mower is full of features to provide maximum productivity. The IS<sup>®</sup> 600Z is capable of tackling tight places, providing maximum manoeuvrability and productivity. You'll mow more lawn in less time.

- Hydro-Gear<sup>®</sup> ZT-3400 transaxle
- Heavy Duty Bumper
- Commercial Turf Series<sup>™</sup> petrol engine
- Roll Over Protection Structure
- Removable floor plate
- **Comes with 4-Year warranty\***



**£10,800**  
PLUS VAT

FM-IS-5901905



SCAN ME FOR MORE ▶

ACCESSORIES	DESCRIPTION	PRODUCT CODE	PRICE
	Lighting kit	F-LIGHTING KIT 2021	<b>£1300.00</b>
	Agricultural tyres EACH	F-K378	<b>£145.00</b>
	Micro beacon	Z-MICRO BEACON KIT	<b>£305.00</b>
	Solid front castor tyres EACH	5109032	<b>£204.00</b>
	Service stand kit	5601078/80	<b>£280.00</b>
	Trailer hitch kit	5600031	<b>£78.00</b>



# IS<sup>®</sup> 600Z

SPECIFICATION	
<b>Engine</b>	
Make	Briggs & Stratton – Petrol
Model	Commercial Series™
Horsepower	27 HP
Cylinders / Displacement	2 Cylinders V-Twin / 810 cc
Cooling	Air cooled
PTO	Electric PTO clutch
Starting	Electric
Fuel Capacity	21 Litres
<b>Mower</b>	
Cutting width (cm/inch)	112 cm / 44" Rear Discharge iCD™
Deck Configuration	Rear discharge/mulching insert and mulching blades
Cutting Height (cm)	3,8 – 11.4 cm
Deck Construction	3,4 mm fabricated construction, full width double top deck, 9,5 mm scuff guards, overlap welded corners
Mower Spindles	Cast aluminium 133 mm; 25,4 mm shaft
Deck lift system	Foot pedal, spring assisted
<b>Suspension &amp; Drive Train</b>	
Suspension	Rear wheel suspension, pivoting front axle with front ride dampening shocks
Transmission	Independent Hydro-Gear® ZT-3400™ transaxles
Drive Axles	28,6 mm Tapered with 4-bolt flange
Drive Tyres (inch)	20 x 8.00 – 10 (4 ply)
Caster Tyres (inch)	11 x 4.00 – 5 (4 ply)
<b>Noise and Vibration</b>	
HAV	< 2.5
WBV	< 0.5
Sound dB(A)	100
<b>Ground Speed</b>	
Speed-fwd. (km/h)	0 – 14.5 km/h
Speed-rev. (km/h)	0 – 6,5 km/h
<b>Dimensions</b>	
Overall length (cm)	203
Overall width (cm)	117
Dry weight (Kgs)	418kg
<b>Operator Control &amp; Comfort Systems</b>	
Roll-Over Protection Structure	Standard, foldable with seat belt
Instrumentation	Fuel level, hour meter
Controls	Seat activated engine kill, PTO clutch safety switch, neutral and parking brake safety circuit
Parking Brake / Safety Circuit	Integrated transaxle brake
<b>Warranty*</b>	
Mower	2-4-Year limited warranty (48 months or 500 hours) whichever occurs first. Unlimited hours during the first 2 years (24 months)
Coil-over-shocks	4-Year Limited warranty (48 months unlimited hours including all suspension related components)
Engine	2-Year Manufacturer's limited warranty
Transmission	2-Year manufacturer's limited warranty
Consumables	90 days (including drive belts, tyres, brakes, deck rollers, battery, blades)

YOUR NEAREST AUTHORISED FERRIS DEALER IS:

[ferrismowers.co.uk](http://ferrismowers.co.uk)