



# IS<sup>®</sup> 6200Z

## Ferris IS<sup>®</sup> 6200Z

Looking for the ultimate workhorse that has an unprecedented level of productivity and is extremely comfortable to operate at the same time? Stop looking any further, you've found it! Its incredible engine power and highly versatile deck design will conquer the most challenging mowing jobs while our exclusive suspension technology reduces the effects of uneven terrain, allowing you to maintain mowing speed and increasing your productivity by getting the job done faster. Because, why decide between getting your work done faster or feeling good when you finish? Ferris got your back on both! With the IS@6200, we set the new industry benchmark for the ultimate riding and cutting machine.

- NEW! iCD+™ Cutting System
- Hercules™ II cast-iron mower spindle
- Dual coil-over-shock rear suspension
- Ferris uses industry leading 6 mm thick frame.
- foot-operated hydraulic deck lift system
- **Comes with 4-Year warranty\***



**£41,500**  
PLUS VAT

FM-IS-5901850



SCAN ME FOR MORE ▶

ACCESSORIES	DESCRIPTION	PRODUCT CODE	PRICE
	Lighting kit (inc. side lights & indicators)	F-LIGHTING KIT 2021	<b>£1300.00</b>
	Service jack, mounting kit, extension sleeve (for 72")	5601080, 5601235, 5601079	<b>£365.00</b>
	Flat free castor wheels	5109903	<b>£260.00</b>
	Agri/cleated tyre	26X12-12AG	<b>£245.00</b>
	Micro beacon	MICRO BEACON KIT	<b>£305.00</b>



# IS<sup>®</sup> 6200Z

SPECIFICATION	
<b>Engine</b>	
Make	Caterpillar
Model	C1.7
Horsepower	8.3 HP
Cylinders / Displacement	3 Cylinders in line /1.699 cc
Cooling	Liquid Cooled
PTO	Electric PTO clutch
Starting	Electric
Fuel Capacity	51 Litres
<b>Mower</b>	
Cutting width (cm/inch)	183 cm / 72" Triple iCD™
Deck Configuration	Configurable deck including: rear discharge, side discharge, mulching and mulching blades
Cutting Height (cm)	3.8 – 15.2 cm
Deck Construction	3,4 mm fabricated construction, full width double top deck, metal scuff guards, reinforced leading edge, overlap welded corners
Mower Spindles	Cast-iron 257 mm; 30,16 mm shaft
Deck lift system	Hydraulic
<b>Suspension &amp; Drive Train</b>	
Suspension	4-Wheel independent suspension
Transmission	Independent Hydro-Gear® PW pumps and Parker TG0335 wheel motors with industrial oil filter and remote oil cooler
Drive Axles	31,75 mm Tapered with 5-bolt wheel hub
Drive Tyres (inch)	26 x 12.00 – 12 (4 ply)
Caster Tyres (inch)	13 x 6.50 – 6 (4 ply)
<b>Noise and Vibration</b>	
HAV	< 2.5
WBV	< 0.5
Sound dB(A)	105
<b>Ground Speed</b>	
Speed-fwd. (km/h)	0 – 20 km/h
Speed-rev. (km/h)	0 – 10 km/h
<b>Dimensions</b>	
Overall length (cm)	229.5
Overall width (cm)	188.5
Dry weight (Kgs)	1158kg
<b>Operator Control &amp; Comfort Systems</b>	
Roll-Over Protection Structure	Standard, foldable
Instrumentation	Fuel level gauge in each tank. Multi-functional color display showing engine functions, machine functions, engine warnings and maintenance reminders
Controls	Independent (left and right) forward & reverse levers, Seat activated engine kill, PTO clutch safety switch, neutral and parking brake safety circuit
Parking Brake / Safety Circuit	Drum type
<b>Warranty*</b>	
Mower	4-Year limited warranty (48 months or 500 hours) whichever occurs first. Unlimited hours during the first 2 years (24 months)
Coil-over-shocks	5-Year (60 months) unlimited hours (including all suspension related components)
Engine	3-Year manufacturer's limited warranty
Transmission	2-Year manufacturer's limited warranty
Consumables	90 days (including drive belts, tyres, brakes, deck rollers, battery, blades)

YOUR NEAREST AUTHORISED FERRIS DEALER IS:

[ferrismowers.co.uk](http://ferrismowers.co.uk)