



SRST™Z1

SRST™Z1 36"

The Soft Ride Stand-on SRST™ Z1 is raising the bar with our patent pending adjustable operator platform, featuring suspension technology, optimising operator comfort and increasing productivity! The superior balance provides stability and manoeuvrability that exceeds expectations for traction and handling. The Soft Ride Stand-on SRST™ Z1 is designed to allow for quick operator exit and re-entry. Need to walk away from the mower to move an obstacle or debris? The PTO will automatically disengage when the operator leaves the platform. Restarting the blades is just as easy. When the operator steps back onto the platform and re engages the PTO switch they can continue mowing.

- Patent pending suspension platform system
- Easy adjustable cutting height
- Generous 23 litres fuel tank
- 3-position speed control
- Commercial Hydro-Gear® ZT-3400® engine
- Ergonomically designed thigh pad
- iCD™ Cutting System
- **Comes with 2-Year warranty***



£11,500
PLUS VAT

SRSZ1KAV1936RDCE



SCAN ME FOR MORE ▶

ACCESSORIES	DESCRIPTION	PRODUCT CODE	PRICE
	Agricultural tyres EACH 36"	23X8.5-12AG	£160.00
	Service stand	5601080/1286	£280.00



SRST™ Z1

SPECIFICATION	
Engine	
Make	Kawasaki – Petrol
Model	FS600V
Horsepower	19,0 HP
Cylinders / Displacement	2 Cylinders V-Twin / 603 cc
Cooling	Air cooled
PTO	Electric PTO clutch
Starting	Electric
Fuel Capacity	23 Litres
Mower	
Cutting width (cm/inch)	91 cm / 36" Rear Discharge
Deck Configuration	Rear discharge/mulching insert and mulching blades
Cutting Height (cm)	44 – 114 mm
Deck Construction	3.4 mm fabricated construction, full width double top deck, 4,8 mm scuff guards, 9.5mm leading edge, overlap welded corners
Mower Spindles	Cast aluminium 133 mm; 25,4 mm shaft
Deck lift system	Hand-operated, spring assisted
Suspension & Drive Train	
Suspension	Patent pending adjustable suspension platform
Transmission	Independent Hydro-Gear® ZT-3400™ transaxles
Drive Axles	28,6 mm Tapered with 4-bolt flange
Drive Tyres (inch)	23 x 8.50 – 12 (4 ply)
Caster Tyres (inch)	11 x 4.00 – 5 (4 ply) Flat free
Noise and Vibration	
HAV	< 2.5
WBV	<0.5
Sound dB(A)	100
Ground Speed	
Speed-fwd. (km/h)	0 – 12,8 km/h
Speed-rev. (km/h)	0 – 6,4 km/h
Dimensions	
Overall length (cm)	162
Overall width (cm)	92
Dry weight (Kgs)	268
Operator Control & Comfort Systems	
Roll-Over Protection Structure	N/A
Instrumentation	Hour meter, fuel level gauge
Controls	Integrated forward & reverse control levers with stability bar, Automatic PTO Restart
Parking Brake / Safety Circuit	Internal transaxle brake / Operator presence in platform, Parking brake safety circuit for starting engine
Warranty*	
Engine	3-Year manufacturer's limited warranty
Transmission	2-Year manufacturer's limited warranty
Balance of machine	4-Year Limited Warranty (48 months) or 500 hours, whichever occurs first. Unlimited hours during the first 2 years (24 months). Coil-over-shocks and all suspension related components are covered for 4 years (48 months) unlimited hours. Belts, Tires, Brake Pads, Battery, Blades: 90 days

YOUR NEAREST AUTHORISED FERRIS DEALER IS:

ferrismowers.co.uk